



Office of the Bids and Awards Committee

August 26, 2026

SUPPLEMENTAL/BID BULLETIN (SBB) NO. 2026-29

This SBB No. 2026-29 for Project ID No. GS-2026-37, **“SUPPLY AND DELIVERY OF CONSTRUCTION SUPPLIES, MATERIALS & EQUIPMENT”** is issued pursuant to Section 51.4 of the Implementing Rules and Regulations of Republic Act No. 12009 (New Government Procurement Act), to clarify, modify or amend items in the Bidding Documents. Accordingly, this shall form an integral part of the Bidding Document.

ITB Clause	PARTICULARS		AMMENDMENT		
ITEM NO.	UNIT	ITEM DESCRIPTION	ITEM NO.	UNIT	ITEM DESCRIPTION
LOT 1		PR# 994 GSO (OASP IMPROVEMENT)	LOT 1		PR# 994 GSO (OASP IMPROVEMENT)
13	box	2.0mm ² TW cu. Wire, stranded, 100 mtrs/box	13	box	2.0mm ² TW cu. Wire, stranded, 150 mtrs/box
14	pcs	Minirib for ceiling, prepainted 1.2m x 2.4m, white	14	pcs	Minirib for ceiling, prepainted 1.2m x 2.4m, 0.3mm thk, white
15	pcs	Minirib moulding 8', white	15	pcs	Minirib moulding 2" X 2" 8' , 0.3mm thk white
16	pcs	Rectangular tube 1" x 2" x 20'	16	pcs	Rectangular tube 2mm thk 2" x 2" x 20'
24	pcs	Paint roller w/ basin	24	pcs	Paint roller 6" w/ basin
25	pcs	Paint tape 1"	25	rolls	Paint tape 1"
LOT 2		PR# 1102 CON	LOT 2		PR# 1102 CON
1	box	TW wire # 14.0 mm ²	1	box	TW copper wire stranded # 14.0 mm ² 150m/box
2	box	TW wire # 5.5 mm ²	2	box	TW copper wire stranded # 5.5 mm ² 150m/box
3	pcs	ACU Circuit Breaker with 3 prong outlet (30-40 amps)	3	pcs	ACU Circuit Breaker with 3 prong outlet (30-40 amps) with housing
4	pcs	EMT Clip 3/4	4	pcs	EMT Clip 3/4"
LOT 3		PR# 522 Sugbahan Function Hall Phase II	LOT 3		PR# 522 Sugbahan Function Hall Phase II
1	sets	Pendant Light, (LLPRT-003 E 27, 280MM Black)	1	sets	Pendant Light, E 27 Socket, 280mm diameter, Adjustable Pendant, Black 
2	sets	Surface Downlight (LLPL-051-E27 220MM GL CLR)	2	sets	Surface Downlight (E27 220MM GL CLR) 

3	sets	Rustic Light, (LLWRT 003-E27, 270MM, Black)	3	sets	Wall Light, E 27 Socket, 280mm diameter, Black 
4	sets	4 pcs Surface type Spotlights (SLH03x3.55-GU10 BLK-LED5W CW)	4	sets	4 PCS Surface Type Spotlights (BLK-LED5W CW) Track Lights, 4 light bulbs, 20 Watts, 220V Light body color: Black Color temperature: Natural White 
5	m	8.0 MM2 THHN Cu. Wire Stranded	5	m	8.0 mm ² THHN Cu. Wire Stranded
6	boxes	2.0 MM2 THHN Cu. Wire Stranded	6	boxes	2.0 mm ² THHN Cu. Wire Stranded 150m/box
7	boxes	3.5 MM2 THHN Cu. Wire Stranded	7	boxes	3.5 mm ² THHN Cu. Wire Stranded 150m/box
LOT 4		PR# 1114 (Crop Enterprise Office)	LOT 4		PR# 1114 (Crop Enterprise Office)
2	piece	Hand Drum/Barrel Pump, Heavy Duty Height:136	2	piece	Hand Drum/Barrel Pump, Heavy Duty Height: 136cm, Steel, 330ml per revolution, Dry Weight: 6.6kg.
5	piece	Padlock	5	piece	Padlock , body width: 50mm
6	roll	Plastic Twine	6	roll	Plastic Twine, Net Weight: 1 kilogram
11	roll	Trapal, Super Thick, 12ft width	11	roll	Trapal, Super Thick, width: 12ft , Length: 320 meters
LOT 5		PR# 1262 VPRDE (DABAR FUNDED)	LOT 5		PR# 1262 VPRDE (DABAR FUNDED)
1	unit	Generator - Diesel operated; 40 kVa; Rated power: 38KW Steady-state frequency adjustment rate: ≤0.5% Output voltage: 400/230V Voltage stabilization time (S): ≤3s Output current: 57.6A Cooling method: closed water circulation forced air cooling Speed regulation method: mechanical speed Technical speed Technical parameters of generator: Motor model: KRS-32 GF Rated power: 32KW Standby power: 38KW Motor type: three-phase AC synchronous generator Voltage regulation method: voltage regulation Protection level: IP23 Wiring method: three-phase four-wire, Y-type connection Rated voltage: 400/230V Frequency: 50HZ Insulation level: F level Excitation; with 1 year warranty on parts and service. free demo on the proper use, care and maintenance, EC Certified.	1	unit	Heavy Duty Generator - Diesel operated; 40 kVa 3 phase generator ; Rated power: 38KW Steady-state frequency adjustment rate: ≤0.5% Output voltage: 400/230V Voltage stabilization time (S): ≤3s Output current: at least 100A Cooling method: closed water circulation forced air cooling Speed regulation method: mechanical speed Technical speed Technical parameters of generator: GF Rated power: 32KW Standby power: 38KW Motor type: three-phase AC synchronous generator Voltage regulation method: voltage regulation Protection level: IP23 Wiring method: three-phase four-wire, Y-type connection Rated voltage: 400/230V Frequency: 50HZ -60 HZ Insulation level: F level Excitation; with 1 year warranty on parts and service. free demo on the proper use, care and maintenance, EC Certified. Supplier must provide fuel for the testing and Commissioning of the Unit

GF			GF		
Lot 6		PR# 1268 GSO (Repair & Improvement of Human Ecology Building)	Lot 6		PR# 1268 GSO (Repair & Improvement of Human Ecology Building)
1	pcs	Metal track 0.4mm thk x2" z 3" x 20'	1	pcs	Metal track 0.4mm thk x2" x 3" x 20'
2	pcs	Metal studs 0.4mm thk x2" z 3" x 20'	2	pcs	Metal studs 0.4mm thk x2" x 3" x 20'
7	pcs	Minirib ceiling moulding 8' white	7	pcs	Minirib ceiling moulding 2"x2"x8' white
8	pcs	Rectangular tube 2mm thk 2" x 2" x 20'	8	pcs	Rectangular tube 2mm thk 2" x 2" x 20'
9	pcs	Prepainted ceiling Minirib 3m, white	9	pcs	Minirib for ceiling, prepainted 1.2m x 3m, white
14	pcs	Prepainted Minirib Roofing 1.0m effect. Width X 7.5m, spanish red	14	pcs	Prepainted Minirib Roofing 1.0m effect. Width X 7.5m, spanish red .3mm thk.
36	pcs	Premium paint brush #4	36	pcs	Premium paint brush 4"
37	pcs	Premium paint roller #6 with out basin	37	pcs	Premium paint roller 6" with basin

For guidance and information of all concerned.


REY F. POLON

BAC, Vice-Chairperson for Goods and Services